



TAN



LIGHT COFFEE



TK TAN



DAWN MIST



MORTAR GRAY



PEARL GRAY



NATURAL CONCRETE



FOLKSTONE



LIGHT GRAY



DARK GRAY



WEATHERED GRAY



TILE RED

## Standard Color Chart

ALSO AVAILABLE IN WHITE AND CUSTOM COLORS

# Standard Product Descriptions

The below products are available in any of the standard colors shown (on front).

## BRIGHT KURE & SEAL

*Item No: TK-BR.K&S series*

A specialized superior curing and sealing compound that is used to cure and highlight exposed aggregate and colored concrete. BRIGHT KURE & SEAL can be combined with TK-TINT PASTE to add color to the concrete and to hide variations among differing concrete shades.

## HI-TECH 2

*Item No: TK-HI TECH 2 series*

A high build, solvent free two-component polyamine epoxy system that is specially designed for concrete floor application where maximum durability and chemical resistance are essential. The high gloss finish is smooth, durable and easy to clean.

## TK-EPOXY COLOR SYSTEM VOC

*Item No: VARIES*

A two-component epoxy color coating for use on concrete. It forms a penetrating, high strength coating that is resistant to abrasion from heavy traffic, chemical attack and rubber burns.

## TK-CCS CONCRETE COLORED STAIN

*Item No: TK-CCS series*

A high solids chlorinated rubber concrete cure and seal and protector, designed to hide variations of shading in concrete that are due to placement and finishing procedures.

## TK-TINT PASTE

*Item No: TK-1100 series*

A color additive specially designed to be added to BRIGHT KURE & SEAL to produce an opaque, tinted cure and seal. In combination, the two products help to hide variations of shading in concrete that are due to variables such as placement, concrete admixes, finishing and weather conditions.

## TK-SILOXANE DYE

*Item No: TK-5765 series*

A pigmented, specially formulated waterproofing treatment that hides discolored and differing color applications of concrete to produce one uniform color.

## TK-TRI-LASTIC

*Item No: TK-5610-5612 series*

A smooth, protective elastomeric acrylic coating for use on concrete, masonry and stucco. TRI-LASTIC provides superior water repellency and maintains its flexibility throughout various weather cycles.

## TK-TRI-SHEEN ACRYLIC

*Item No: TK-5342 series*

A breathable masonry coating that is designed to be used on all cementitious surfaces. TRI-SHEEN ACRYLIC may be used as a topcoat over TRI-SHEEN CONCRETE SURFACER or may be used on its own. It has superior exterior durability and adhesion.

## TK-TRI-SHEEN ACRYLIC STAIN

*Item No: TK-5609 series*

A medium viscosity, opaque acrylic emulsion designed exclusively for wood or wood-like surfaces. TRI-SHEEN ACRYLIC STAIN forms a breathable film that allows trapped moisture to escape while providing a durable and weather resistant film.

## TK-TRI-SHEEN CONCRETE SURFACER

*Item No: TK-5321 series*

A non-cementitious, acrylic, breathable masonry coating that can be used on any properly prepared cementitious-type surface for enhanced durability and beauty.

## TK-TRI-SHEEN PIGMENTED STAIN

*Item No: 5272 series*

A low viscosity, semi-opaque acrylic emulsion designed specially for cementitious surfaces. TRI-SHEEN PIGMENTED STAIN forms a breathable film that allows trapped moisture to escape, while aiding in color uniformity and retention.

**DISCLAIMER:** The examples shown are representations only. Variations in color may occur due to surface texture, substrate absorption, product thickness and light source. Product finish and gloss will vary by product. Color draw downs are available through TK Products for color approval. It is always recommended to apply a mock-up to the actual surface to be coated in order to ensure color approval prior to project start-up.



ADVANCED CONCRETE COATING SOLUTIONS

11400 W. 47th Street Minnetonka, MN 55343

800-441-2129 toll free • 952-938-8084 fax • [www.tkproducts.com](http://www.tkproducts.com)

ISO 9001 CERTIFIED

© 2017