

DECEMBER 10, 2014

TK-AIRMAX 2105 VAPOR PERMEABLE AIR BARRIER

Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation

TK-AIRMAX® 2105 VAPOR PERMEABLE AIR BARRIER is a high solids, solvent-borne, elastomeric, spray applied flexible air barrier and water vapor permeable membrane for all types of cavity wall construction. It meets or exceeds ASTM E-2178 for air leakage and ASTM E-96 for water vapor permeability.

TK Products certifies the following information for TK-AIRMAX® 2105 VAPOR PERMEABLE AIR BARRIER:

Regional Materials

TK-AIRMAX® 2105 VAPOR PERMEABLE AIR BARRIER is manufactured in Minnetonka, MN 55343.

VOC Content

TK Products certifies that the VOC (Volatile Organic Content) of TK-AIRMAX® 2105 VAPOR PERMEABLE AIR BARRIER is 97.5 g/L.

Based upon the above information, TK Products certifies that TK-AIRMAX® 2105 VAPOR PERMEABLE AIR BARRIER may contribute to the following LEED NC Credits:

- **EA Credit 1: Optimize Energy Performance**
- **IEQ Credit 4.2: Low -Emitting Materials: Paint and Coating**
- **IEQ Credit 7.1: Thermal Comfort: Design**

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council