



TK-TRI-BOND
Bonding Agent

Item No. TK-TRIBOND

PRODUCT DESCRIPTION

TK-TRI-BOND is a liquid, ready to use, high build, reemulsifiable bonding agent for adhering gypsum plaster and Portland cement mixtures to a variety of surfaces.

- Non-flammable and contains no volatile organic solvents.
- High tensile and shear strength
- Non-reactive to plaster/cement alkalinity
- May be applied to either damp or dry surfaces
- Withstands environments ranging from -40°F to 300°F
- Unaffected by humidity or condensation when thoroughly dried

USES:

Suitable for interior or exterior use to bond a variety of cementitious and gypsum materials (new concrete, mortar, stucco, plaster) to new or existing wallboard, fiber board, wood, metal, glass, tile, concrete, masonry and marble.

APPLICATION PROCEDURES

PREPARATION:

Surfaces must be structurally sound. Remove all dust, rust, laitance, mildew, dirt, oil, grease, wax, forming agents, curing compounds or any substances which may affect proper bonding. Smooth surfaces should be abraded to ensure proper adhesion. Apply a small test patch and allow to dry thoroughly to check for peeling or curling.

APPLICATION:

Stir TK-TRI-BOND thoroughly before using. Do not dilute. Apply by spray, roller or brush making certain to leave a thin and continuous film. Do not allow the product to puddle in low-lying areas.

IMPORTANT: Allow TK-TRI-BOND to become tack-free before applying wet plaster or cementitious materials. Material may be applied up to 3 days after application of TK-TRI-BOND provided that the film is still clean. Cementitious toppings must be a minimum of 1/2" thick to obtain maximum adhesion. Use TK-LIQUID BONDING AGENT 225* in the mixing liquid of the new cementitious material.

CLEAN UP:

Wash tools immediately with clean water. Dried material may become difficult to remove.

COVERAGE:

Typical coverage rate is 200-300 square feet per gallon.

Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

LIMITATIONS:

- Do not use in areas where extended periods of moisture are present (i.e. swimming pools, cisterns or areas of standing water)
- Do not apply to frozen surfaces or when temperatures will drop below 40°F within 4 hours of application
- Do not allow to freeze. If the material does freeze, it should be immediately moved to a warmer area to thaw. If TK-TRI-BOND returns to a smooth liquid upon thawing and stirring, then its bonding qualities have not been impaired.

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

TECHNICAL DATA	
Weight Per Gallon:	9.05 lbs
Specific Gravity:	1.1
Viscosity:	68 KU
Average Dry Time (70°F):	1 hour (approximate)
Freeze/Thaw Stability:	5 cycles
pH:	4.5
VOC Content:	< 350 g/l
A.I.M. Category:	Primers and Undercoaters Maximum VOC 350 g/l
Applicable Standards:	-ASTM C1059, Type I, Redispersable -ASTM C631 -MIL-B-19235 (DOCKS)

continued on next page...

AVAILABILITY:

TK-TRI-BOND is available through TK Distributors. Contact TK Products for the nearest distributor. Packaged in 55-gallon drums, 5-gallon pails and 1-gallon cans.

FOR PROFESSIONAL USE ONLY

NOTES

**TK-LIQUID BONDING AGENT 225 must be purchased separately.*

04/15 Last Rev. 02/15

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. **SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED.** TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.



TK Products
11400 West 47th Street Minnetonka, MN 55343
800-441-2129 toll free | 952-938-8084 fax | www.tkproducts.com