

APRIL 9, 2009

AK-2 ACHRO KURE WB

Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation

AK-2 ACHRO KURE WB is a waterborne acrylic membrane-forming polymer for curing and sealing new and existing concrete. It is particularly recommended for use in occupied areas where solvent systems are often objectionable. AK-2 ACHRO KURE WB meets or exceeds the following standards: ASTM C-309, Type I, Class A & B, AASHTO M-148 Type I, USDA, and is compatible with carpet and resilient tile adhesives.

TK Products certifies the following information for AK-2 ACHRO KURE WB:

Manufacturing Location

AK-2 ACHRO KURE WB is manufactured in Minnetonka, MN.

Recycled Content

AK-2 ACHRO KURE WB is manufactured with 6% of pre-consumer material recycled content from the normal recovery of raw material in the manufacturing process.

VOC Content

TK Products certifies that the VOC (volatile organic content) of AK-2 ACHRO KURE WB is 170g/l.

Based upon the above information, TK Products certifies that AK-2 ACHRO KURE WB may contribute to the following LEED NC v2.2 Credits:

- MR Credits 1.1 & 1.2: Building Reuse: Maintain 75% & 95% of Existing Walls, Floors, & Roof
- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured Regionally
- EQ Credit 4.2: Low – Emitting Material: Paints and Coatings (referencing the South Coast Air Quality Management District (SCAQMD) Rule 1113, in effect on January 1, 2004)

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council