

APRIL 9, 2009

TK-2519 DC WB

Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation

TK-2519 DC WB is a 100% resin base concrete curing compound in mineral spirits and water, typically used when it is known that the concrete will receive a treatment at a later date where it is undesirable to have a curing compound present. TK-2519 DC WB is designed to dissipate in approximately 30 days. It meets or exceeds ASTM C-309 Type I, Class B, and AASHTO M-148 Type I, Class B.

TK Products certifies the following information for TK-2519 DC WB:

Manufacturing Location

TK-2519 DC WB is manufactured in Minnetonka, MN.

Recycled Content

TK-2519 DC WB is manufactured with 6% of pre-consumer material recycled content from the normal recovery of raw material in the manufacturing process.

VOC Content

TK Products certifies that the VOC (volatile organic content) of TK-2519 DC WB is 267g/l.

Based upon the above information, TK Products certifies that TK-2519 DC WB may contribute to the following LEED NC v2.2 Credits:

- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured Regionally
- EQ Credit 4.2: Low – Emitting Material: Paints and Coatings (referencing the South Coast Air Quality Management District (SCAQMD) Rule 1113, in effect on January 1, 2004)

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council