

TK-CLEAR EMULSION LINSEED OIL L368

Curing and Sealing Compound

Item No. TK-L368 CL

PRODUCT DESCRIPTION

TK-CLEAR EMULSION LINSEED OIL L368 is a clear linseed oil emulsion for curing, sealing and protecting new exterior concrete.

Features:

- Controls moisture loss and aids in hydrating cement during the curing process.
- Provides a quality protective coating that prevents damage from deicing chemicals and freeze/thaw cycles.
- Formulated to meet state highway department requirements.

USES:

Suitable for exterior use on any freshly poured concrete surface where good curing qualities and a protective coating are desired.

APPLICATION PROCEDURES:

MIXING:

The material is ready for use but should be stirred prior to use. Do not dilute.

APPLICATION:

Apply with conventional spray equipment immediately once finish troweling is complete and surface water has dissipated. Apply in a uniform manner and at a rate to satisfy the porosity of the concrete. Maintain a wet edge and stop at natural break points to prevent lap marks. Let dry overnight.

CLEAN UP

Clean tools and equipment with soap and water before the material dries. If the material has dried, it may be removed with mineral spirits.

COVERAGE:

Typical coverage rate is 200 square feet per gallon. Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

LIMITATIONS:

- Do not over apply.
- This product is intended for exterior use only.
- Not for use on asphalt or where spillage of solvents, fuels, brake or transmission fluids are expected.
- Do not use if further coatings or coverings will be desired, unless said coating is a linseed oil anti-spalling compound such as TK-CONCRETE TREATING OIL 3102.
- Protect from freezing and store at temperatures above 40°F.
- Sprayers should be equipped with neoprene hose, gaskets and washers.

TECHNICAL DATA

Color:	Clear
Oil Phase %:	50% +/- 1
Water Phase %:	50% +/- 1
Viscosity:	55-60
Weight per Gallon:	8.68 lbs.
VOC Content:	< 700 g/l
A.I.M. Category:	Concrete Curing & Sealing Compound Maximum VOC 700 g/l
Applicable Standards:	-ASTM C-309, Type 1, Class -AASHTO Des. M-148, Type 1, Clear

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

AVAILABILITY:

TK-CLEAR EMULSION LINSEED OIL L368 is available through TK Distributors. Contact TK Products for the nearest distributor.

Packaged in 55-gallon drums, 5-gallon pails and 1-gallon cans.

FOR PROFESSIONAL USE ONLY

03/15 Last Rev. 09/14

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.



TK Products Construction Coatings

11400 West 47th Street Minnetonka, MN 55343
800-441-2129 toll free | 952-938-8084 fax | www.tkproducts.com