

JANUARY 4, 2010

## **TK-5609 TRI-SHEEN ACRYLIC STAIN**

### ***Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation***

TK-5609 TRI-SHEEN ACRYLIC STAIN is a water-borne opaque stain designed especially for wood surfaces. Tri-Sheen Acrylic Stain has a breathable film with superior resistance to UV, the weather and elements, and grain cracking.

### ***TK Products certifies the following information for TK-5609 TRI-SHEEN ACRYLIC STAIN:***

#### **Manufacturing Location**

TK-5609 TRI-SHEEN ACRYLIC STAIN is manufactured in Minnetonka, MN.

#### **Regional Materials**

20% by weight of TK-5609 TRI-SHEEN ACRYLIC STAIN was produced with regionally extracted and processed materials.

#### **Recycled Content**

TK-5609 TRI-SHEEN ACRYLIC STAIN is manufactured with 6% combined recycled content.

#### **VOC Content**

TK Products certifies that the VOC (volatile organic content) of TK-5609 TRI-SHEEN ACRYLIC STAIN is 104g/l.

### ***Based upon the above information, TK Products certifies that TK-5609 TRI-SHEEN ACRYLIC STAIN may contribute to the following LEED NC v2.2 Credits:***

- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured Regionally
- EQ Credit 4.2: Low – Emitting Material: Paints and Coatings (referencing the South Coast Air Quality Management District (SCAQMD) Rule 1113, in effect on January 1, 2004)

Respectfully,



LEED Administrator  
TK Products  
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council