



TK-CONCRETE STAIN WB 3150

Item No. TK-3150 series

PRODUCT DESCRIPTION

TK-CONCRETE STAIN WB 3150 is a water-borne, single component, solid colored stain to beautify and protect concrete and masonry surfaces. TK-CONCRETE STAIN WB 3150 acts as a barrier against damaging substances such as acids and oils, all while imparting a long-lasting, attractive painted-look finish.

Features:

- Results in a painted-look finish that is as rugged as it is beautiful.
- Environmentally-friendly formulation with low VOC (volatile organic compound) content.
- Bonds with the surface to provide a barrier against acids, alkali, gas, oil and ultraviolet rays.
- Will not chip, peel, flake or fade.
- Provides color uniformity and long-lasting color retention.
- Offers improved resistance to wear and abrasion over standard finish coatings.
- May be top coated with a variety of sealers for professionally finished results.
- Single component and fast drying for quick, easy application.

USES:

Suitable for interior or exterior use on vertical or horizontal cementitious surfaces. May be applied to either bare or previously painted surfaces. Ideal for beautifying patios, walkways, pool decks, basement floors, block and stucco walls and garage floors*.

**For best performance on garage floors, use TK's Epoxy or Polyaspartic flooring systems.*

APPLICATION PROCEDURES

PREPARATION:

Surfaces must be clean, dry and in sound condition prior to application. Any needed repairs should be complete before staining. Any grease, oil or other surface contaminants should be removed either by spot cleaning with TK-CHEMICAL CLEANER 101*, or by using a bleach/water solution (1-cup household bleach to 1-gallon of water) to kill and remove mold, mildew or fungus. Allow surfaces to dry for 24 hours and ensure that prepared surfaces have a pH level between 6-10 before applying.

Special Surface Preparation Instructions:

Bare Concrete - Newly poured concrete must be allowed 28 days to cure prior to application. Do NOT apply the stain until all surfaces are porous.

Painted Concrete - Any peeling or flaking paint must be removed. Intact paint should be rough sanded using a circular motion and the resulting sanding dusts rinsed away to ensure proper adhesion. DO NOT ETCH PREVIOUSLY PAINTED SURFACES.

Steel Troweled Surfaces - Steel troweled surfaces should be acid etched or shot blasted to promote better adhesion.

Horizontal Surfaces - Horizontal surfaces must be etched with either an etching solution or muriatic acid (follow label instructions). The surface should mimic the feel of 50-grit sandpaper upon completion. If it does not, a second etching will be required.

Vertical Surfaces - Vertical surfaces should absorb water. To test, spray water directly onto various sections of the surface to be stained. If the water does not absorb rapidly, either the surface should be acid etched using an etching solution or the surface should be mechanically abraded.

MIXING:

- 1) TK-CONCRETE STAIN WB 3150 is supplied ready to use but should be stirred prior to use to eliminate any phase separation or settling which may occur upon storage or shipping.
- 2) When using more than one container of this product, be sure to intermix ALL containers together to ensure color uniformity between them.

APPLICATION:

Apply by airless spray, roller or brush in a uniform manner and at the recommended application rate - typically 200 square feet per gallon. Stop at natural break points such as corners and control joints and maintain a wet edge to prevent lap marks. A minimum of two coats is required.

Where a glossy finish is desired, TK-CONCRETE STAIN WB 3150 may be top coated with TK-BRIGHT SEAL WB*.

continued on next page...

TECHNICAL DATA	
Gloss at 60°:	20
Solids by Weight:	39-40%
Viscosity @ 77°F:	65-67 KU
Drying Time:	
Tack Free:	30 minutes-1 hour
Recoat:	1-2 hours
Open to Traffic:	24 hours
V.O.C. Content:	< 350 g/l
A.I.M. Category:	Stains, Opaque Maximum VOC 350 g/l

CLEAN UP:

Clean tools and spills with soap and warm water before the material dries.

COVERAGE:

Typical coverage rate is 200 square feet per gallon.

Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

LIMITATIONS:

- TK-CONCRETE STAIN WB 3150 may be applied over existing coatings provided the coating is ground with an 80-100 grit sand paper or sanding screen prior to application.
- TK-CONCRETE STAIN WB 3150 should not be applied over form oils.
- Do not apply if rain is expected within 12 hours of application.

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

AVAILABILITY:

TK-CONCRETE STAIN WB 3150 is available through TK Distributors. Contact TK Products for the nearest distributor.

Available in 9 standard colors, or custom colors may be produced upon request (please allow 2-3 weeks for custom colors to be produced).

Packaged in 5-gallon pails and 1-gallon cans.

FOR PROFESSIONAL USE ONLY

NOTES:

*TK-CHEMICAL CLEANER 101 must be purchased separately

*TK-BRIGHT SEAL WB must be purchased separately

02/15 Last Rev. 09/14

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. **SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED.** TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.