

APRIL 24, 2009

TK-211 EPOXY PATCH

Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation

TK-211 EPOXY PATCH is a two-component trowelable epoxy-patching compound for concrete surfaces. Fine silica or coarse aggregate may be used as an extender to provide skid proof surfaces and better economics. TK-211 EPOXY PATCH has excellent resistance to deicing salts, abrasion, and petroleum products, and meets the following standards: ASTM C-881 Type I & II, ASTM D638, ASTM D570.

TK Products certifies the following information for TK-211 EPOXY PATCH:

Manufacturing Location

TK-211 EPOXY PATCH is manufactured in Minnetonka, MN.

Recycled Content

TK-211 EPOXY PATCH is manufactured with 6% of pre-consumer material recycled content from the normal recovery of raw material in the manufacturing process.

VOC Content

TK Products certifies that the VOC (volatile organic content) of TK-211 EPOXY PATCH is 0 g/l.

Based upon the above information, TK Products certifies that TK-211 EPOXY PATCH may contribute to the following LEED NC v2.2 Credits:

- MR Credits 1.1 & 1.2: Building Reuse: Maintain 75% & 95% of Existing Walls, Floors, & Roof
- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council