Page: 1 of 5 Process Time: 10:26 am

Date Revised: 3/15/10 Date Printed: 4/8/15

MANUFACTURER: SIERRA CORP/TK PRODUCTS EMERGENCY PHONE: 1-800-424-9300 ADDRESS: 11400 WEST 47TH STREET INFORMATION PHONE: (952)938-7223 MINNETONKA, MN 55343 NAME OF PREPARER: Safety Director

PRODUCT NAME: EPOXY PATCH PASTE

PRODUCT CODE: TK-411 A&B

HAZARD RISK CLASSIFICATION

SIGNAL WORD: DANGER

PICTOGRAM:

GHS05 - CORROSION GHS07 - EXCLAMATION MARK GHS08 - HEALTH HAZARD GHS09 -

ENVIRONMENT

HAZARD CLASS HAZARD CATEGORY

ACUTE TOXICITY CATEGORY 3 ORAL ACUTE TOXICITY CATEGORY 3 DERMAL CATEGORY 3 INHALATION ACUTE TOXICITY

SKIN CORROSION / CATEGORY 1

IRRITATION

SERIOUS EYE DAMAGE / CATEGORY 1

EYE IRRITATION

RESPIRATORY SENSITIZER CATEGORY 1 SKIN SENSITIZER CATEGORY 1 CATEGORY 2 TOXIC TO REPRODUCTION TOXIC TO SPECIFIC TARGET ORGAN CATEGORY 3

TOXICITY - SINGLE EXPOSURE

HAZARDOUS TO THE AQUATIC CHRONIC 2

ENVIRONMENT LONG-TERM (CHRONIC)

HAZARD STATEMENTS:

H301 Toxic if swallowed

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled

H311 Toxic in contact with skin

Causes severe skin burns and eye damage May cause allergic skin reaction H314

H317

Causes serious eye damage Toxic if inhaled H318

H331

H334 May cause allergy or asthma symptoms or breathing difficulties if

inhaled

н335 May cause respiratory irritation

н361 Suspected of damaging fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

PREVENTION:

P201

Obtain special instructions belove use.

Do not handle until all safety precautions have been read and P202

understood.

P231 Handle and store contents under inert gas.

Do not breath dusts/fume/gas/mist/vapors or spray. P260

P264 Wash hands and any exposed area thoroughly after handling.

P270 Do not eat, drink or smoke while using this product.

SAFETY DATA SHEET

Page: 2 of 5
Process Time: 10:26 am

Date Revised: 3/15/10 Date Printed: 4/8/15

P271 Use only outdoors or in well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the

workplace.

P273 Avoid release to the environment.

P281 Use appropriate personal protective impervious gloves/protective

clothing/ OSHA approved eye protection/ face protection.

P285 In case of inadequate ventilation wear appropriate organic vapor

respiratory protection.

RESPONSE:

P301+P310 If swallowed: Immediately call a Poison Center / doctor.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated

clothing. Rinse skin with water (or shower).

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 If exposed or concerned: Get medical advice / attention.

P310 Immediately call a POISON CENTER/doctor/ emergency responder.

P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see on this label)
P322 Specific measures (see on this label)

P330 Rinse mouth.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a Poison

Center/doctor.

P361+P363 Take off immediately all contaminated clothing and wash before

reuse.

P363 Wash contaminated clothing before reuse.

STORAGE:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

DISPOSAL:

P501 Store separately. Dispose of contents/ container in accordance with local/ regional/national /international regulations.

======== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS ========== WEIGHT EXPOSURE LIMITS PERCENT OSHA PEL ACGIH TLV OTHER COMPONENT CAS NUMBER 25068-38-6 25-50 Epichlorohydrin Copolymer NOT ESTABLISHED Wollastonite 13983-17-0 25-50 5 MG/M3 3 MG/M3 * Polyethylenepolyamine Adduct 68953-36-6 10-25 NOT ESTABLISHED 4-Nonyl Hydroxybenzene, Nonylphenol 84852-15-3 10-25 NOT ESTABLISHED Silicone Dioxide 1-10 N/A 6 MG/M3 3 MG/M3 Aliphatic Amine 90-72-2 1-10 5 PPM (SKIN)

+ Bisphenol A 80-05-7 1.7

SAFETY DATA SHEET

Page: 3 of 5 Process Time: 10:26 am

Date Revised: 3/15/10 Date Printed: 4/8/15

			1 PPM 1 PPM
* Tetraethylenepentamine	112-57-2	1-10	
			300 MG/M3

- * Chemical(s) that are chronic health hazards. Refer to section 3 for further information.
- + Toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

PRIMARY ROUTES OF EXPOSURE:

Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Corrosive to eyes. Contact with eyes may cause severe irritation and burns.

SKIN: Corrosive to skin and mucous membranes. Contact with skin may cause severe irritation and burns. May be absorbed through skin in toxic amounts.

INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful. Can cause gastrointestinal irritation, nausea, vomitting and diarrhea. Small amounts aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury.

CHRONIC HEALTH EFFECTS:

medical attention.

Although some components may indicate chronic exposure effects, no effects are anticipated under normal use conditions due to the relatively low proportion in the total mixture.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing.

INGESTION: If a large amount is ingested, give water or milk and induce vomitting. Seek medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.4

UPPER: n/a

EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communicatin Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

Page: 4 of 5 Process Time: 10:26 am

Date Revised: 3/15/10 Date Printed: 4/8/15

STORAGE INFORMATION:

Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see section 10). Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

OTHER PRECAUTIONS:

All empty containers should be disposed of in an evironmentally safe manner in accordance with all governmental regulations.

No special requirements under normal use conditions. In confined areas, or ares with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION:

General room ventilation is adequate.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidlines.

======== SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES ===========

PHYSICAL STATE: Liquid

COLOR: Various colors

ODOR: Odorless.

SOLUBILITY IN WATER: Insoluble/Negligible

SPECIFIC GRAVITY (H2O=1): 1.31

VAPOR DENSITY: Heavier than air.

EVAPORATION RATE: Slower than nBuAc

BOILING RANGE:

COATING V.O.C.: 0 g/l (0.0 lb/gl)

QTARTITTY

Stable under normal conditions and handling.

CONDITIONS TO AVOID:

None known

INCOMPATIBILITY (MATERIALS TO AVOID):

Avoid exposure to strong oxidizing agents and reducing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

HAZARDOUS POLYMERIZATION:

Will not occur.

Product is a skin sensitizer; sensitization can be severe in susceptible individuals.

CARCINOGENICITY

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

ENVIRONMENTAL DATA:

SAFETY DATA SHEET

Page: 5 of 5 Process Time: 10:26 am

Date Revised: 3/15/10 Date Printed: 4/8/15

Although no information is available for this specific product mixture, individual components may by themselves may have ecological affects. Nonylphenol is a marine pollutant.

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

UN3066, Paint, 8, III

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Subatances Control Act (TSCA) chemical substance inventory.

This product does contain a chemical(s) subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372). See section 2.

STATE SPECIFIC REQUIREMENTS:

This product contains a chemical(s) known to the state of California to cause cancer, birth defects or reproductive harm, which are subject to the requirements of California Proposition 65.

Phenylglycidyl ether (trace amounts)

STATE LISTED COMPONENTSCAS NUMBERSTATE CODEPhenylglycidyl Ether122-60-1CABisphenol80-05-7CA, MA, NJ, PA

REVISION DATE: 03/15/10

HMIS CODES: H F R P
3 * 1 0 B