

March 31,2020

[TK-AIRMAX 2103 NON-PERMEABLE WB AIR/VAPOR BARRIER](#)

Product Information Statement for LEED® v.4 Credit Documentation

TK-AIRMAX® 2103 NON-PERMEABLE WB AIR/VAPOR BARRIER is a waterborne spray applied flexible air/vapor barrier membrane for all types of cavity wall construction. It meets or exceeds ASTM E-2178 for air leakage and ASTM E-96 for water vapor permeability.

Use of air barrier systems may contribute to the attainment of LEED® Energy and Atmosphere and Indoor Environmental Quality credits as part of the overall building design.

TK Products certifies the following information for TK-AIRMAX® 2103 NON-PERMEABLE AIR/VAPOR BARRIER:

MR Credit Building Product Disclosure and Optimization- Environmental Product Declarations

An Environmental Product Declaration (EPD) is not available for TK-AIRMAX® 2103 NON-PERMEABLE AIR/VAPOR BARRIER.

MR Credit Building Product Disclosure and Optimization- Sourcing of Raw Materials

Raw Material Source and Extraction Reporting is not available for TK-AIRMAX® 2103 NON-PERMEABLE AIR/VAPOR BARRIER. TK-AIRMAX® 2103 NON-PERMEABLE AIR/VAPOR BARRIER is manufactured in Minnetonka, MN.

TK-AIRMAX® 2103 NON-PERMEABLE AIR/VAPOR BARRIER is manufactured with 3% recycled/bio-based materials.

EQ Credit Low-Emitting Materials

TK-AIRMAX® 2103 NON-PERMEABLE AIR/VAPOR BARRIER has a VOC content of 77.1 g/l. It is compliant under the U.S. National AIM rule, LADCO, OTC Phase I&II, CARB 2007 SCM, and SCAQMD rule 1113.

Emissions Test Reporting is not available for TK-AIRMAX® 2103 NON-PERMEABLE AIR/VAPOR BARRIER



Respectfully,

LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council

ADVANCED CONCRETE COATING SOLUTIONS