

JANUARY 19, 2010

TRI-KOTE 26 UV

Product Information Statement for LEED[®] New Construction (NC) Version 2.2 Credit Documentation

TRI-KOTE 26 UV is a clear chlorinated rubber epoxy concrete treatment for curing, sealing, and hardening freshly placed concrete such as curbs, gutters, sidewalks, bridge decks, median barriers, and sealing/dustproofing existing concrete. TRI-KOTE 26 UV contains additional UV inhibitors to prevent discoloration. TRI-KOTE 26 UV meets or exceeds the following specifications: ASTM C-1315-95, Type I, Class A, B, & C, TT-C-0800A, Type I, Class II, ASTM C-309, Type I, Class A & B, AASHTO Des.M-148, Type I, State DOT's, USDA.

TK Products certifies the following information for TRI-KOTE 26 UV:

Manufacturing Location

TRI-KOTE 26 is manufactured in Minnetonka, MN.

Recycled Content

TRI-KOTE 26 UV is manufactured with 6% of pre-consumer recycled content from the normal recovery of raw material in the manufacturing process.

VOC Content

TK Products certifies that the VOC (volatile organic content) of TRI-KOTE 26 UV is 697g/l.

Based upon the above information, TK Products certifies that TRI-KOTE 26 UV may contribute to the following LEED NC v2.2 Credits:

- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council