Date Revised: 10/22/13

Date Printed: 4/8/15

	======================================					
	SIERRA CORP/TK PRODUCTS EMERGENCY PHONE: 1-800-424-9300					
ADDRESS :	11400 WEST 47TH STREET INFORMATION PHONE: (952)938-7223					
	MINNETONKA, MN 55343 NAME OF PREPARER : Safety Director					
	TRI-SHEEN STAIN PLUS, FED #33522					
PRODUCT CODE: !	TK-52/5-02 ======= SECTION 2 - HAZARDS IDENTIFICATION ====================================					
HAZARD RISK CL						
SIGNAL WORD: W						
PICTOGRAM:						
GHS07 - EXCLAM	ATION MARK					
HAZARD CLASS	HAZARD CATEGORY					
ACUTE TOXICITY	CATEGORY 4 INHALATION					
SKIN CORROSION	/ CATEGORY 2					
IRRITATION						
SERIOUS EYE DAI EYE IRRITATION	•					
TOXIC TO SPECIE	FIC TARGET ORGAN CATEGORY 3					
TOXICITY - SING	GLE EXPOSURE					
HAZARD STATEME						
H303	May be harmful if swallowed					
H315	Causes skin irritation					
H319	Causes serious eye irritation.					
	Harmful if inhaled					
H335 # Chemical(c)	May cause respiratory irritation					
	which may be considered a cancer hazard by IARC and/or NTP. on 11 for further information.					
PRECAUTIONARY	STATEMENTS:					
PREVENTION:						
P261	Avoid breathing dust/fume/gas/mist/vapor/ spray.					
P264	Wash hands and any exposed area thoroughly after handling.					
P271	Use only outdoors or in well-ventilated area.					
P280	Wear protective impervious gloves/ OSHA approved eye					
protection/face	e protection.					
RESPONSE :						
P301+P312	If swallowed: Call a Poison Center / doctor if you feel unwell.					
P302+P352	If on skin: Wash with plenty of water.					
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for					
breathing.						
	If in eyes: Rinse cautiously with water for several minutes.					
	t lenses, if present and easy to do. Continue rinsing.					
P312	Call a POISON CENTER/doctor if you feel unwell.					
P321	Specific treatment (see on this label)					
P330	Rinse mouth.					
P332+P313	If skin irritation occurs: Get medical advice/attention.					
P337+P313	If eye irritation persists: Get medical advice/attention.					
P363	Wash contaminated clothing before reuse.					
STORAGE :						

STORAGE :

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Date Revised: 10/22/13

....

Date Printed: 4/8/15

# P405 Store locked up.

# DISPOSAL:

# P501 Store separately. Dispose of contents/ container in accordance with local/ regional/national /international regulations.

	SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS ====================================
COMPONENT	CAS NUMBER PERCENT OSHA PEL ACGIH TLV OTHER
Titanium Dioxide	13463-67-7 10-25
	10 mg/m3 10 mg/m3
Wollastonite	13983-17-0 1-10
	5 MG/M3 3 MG/M3
# Cristobalite	14464-46-1 .6
	10 MG/M3

\* Chemical(s) that are chronic health hazards. Refer to section 3 for further information.

#### PRIMARY ROUTES OF EXPOSURE:

Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Direct contact with eyes may cause irritation.

SKIN: Prolonged or repeated contact may cause irritation.INHALATION: Inhalation of vapor or mist can cause

irritation of nose, throat and lungs and lead to headaches and nausea.

# INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful.

CHRONIC HEALTH EFFECTS:

Although some components may indicate chronic exposure effects, no effects are anticipated under normal use conditions due to the relatively low proportion in the total mixture.

#### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

### 

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing.

INGESTION: If a large amount is ingested, give water or milk and induce vomitting. Seek medical attention. INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

	SECTION 5 -	FIRE AND	EXPLOSION	HAZARD	DATA	
FLASH POINT: No flash			METHOD USED: 1	n/a		
FLAMMABLE LIMITS IN AIR BY	VOLUME- LOWER: n/a	1		UPPER	: n/a	

EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

#### SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

#### UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

## 

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or

# Date Revised: 10/22/13

# Date Printed: 4/8/15

similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

## HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communicatin Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

#### STORAGE INFORMATION:

Keep from freezing; material may coagulate. The minimum recommended storage temperature is 34F/1C, the maximum recommended storage temperature is 120F/49C. Keep away from incompatable materials (see section 10). Keep containers tightly closed. It is advised that material be used within 1 year of manufacture, rotate stock.

#### OTHER PRECAUTIONS:

All empty containers should be disposed of in an evironmentally safe manner in accordance with all governmental regulations.

## = SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION ==========

#### RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or ares with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

#### VENTILATION:

General room ventilation is adequate.

#### PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

#### EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

#### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

#### WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidlines.

======================================	L AND CHEMICAL PROPERTIES ===============			
PHYSICAL STATE: Liquid	COLOR: Various colors			
ODOR: Amine or ammonia odor	SOLUBILITY IN WATER: Dilutable			
SPECIFIC GRAVITY (H2O=1): 1.23	VAPOR DENSITY: Heavier than air.			
BOILING RANGE:	EVAPORATION RATE: Slower than nBuAc			
COATING V.O.C.: 76 g/l (0.63 lb/gl )				

## 

## STABILITY:

Stable under normal conditions and handling.

## CONDITIONS TO AVOID:

None known

#### INCOMPATIBILITY (MATERIALS TO AVOID):

None known. Materials which are not compatable with water or ordinary organics will not be compatable with this material.

# HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

#### HAZARDOUS POLYMERIZATION:

Will not occur.

SENSITIZATION: None known.

# CARCINOGENICITY:

# SAFETY DATA SHEET

Date Printed: 4/8/15

# Date Revised: 10/22/13

The indicated chemical(s) is listed by ICGIH, NTP, or OSHA as a known human carcinogen (See section 2).

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

## TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

#### MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

# 

#### ENVIRONMENTAL DATA:

Contains ammonia or amines which may be toxic to aquatic life.

CAS NUMBER

**This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261,** however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

## 

SHIPPING NAME:

Not regulated.

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Subatances Control Act (TSCA) chemical substance inventory.

This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372) above de minimis concentrations.

#### STATE SPECIFIC REQUIREMENTS:

STATE LISTED COMPONENTS

This product contains a chemical(s) known to the state of California to cause cancer, birth defects or reproductive harm, which are subject to the requirements of California Proposition 65.

STATE CODE