



TK-EPOXY CRACK & JOINT FILLER

Concrete Crack and Joint Filler

Item No. TK-9010

PRODUCT DESCRIPTION

TK-EPOXY CRACK & JOINT FILLER is a fast setting, semi-rigid, two-component epoxy system for filling control and construction joints in concrete flooring.

Features:

- Epoxy formulation allows it to be used in damp areas where comparable urethane/polyurea joint fillers cannot be used.
- Gels in less than 10 minutes and is tack free in under an hour.
- Extremely low VOC content (< 1 g/l)

USES:

Suitable for interior or exterior use to fill joints in warehouse, industrial and commercial concrete flooring. May also be used to fill cracks on older concrete floors.

APPLICATION PROCEDURES:

PREPARATION:

Cracks and joints should be clean and dry. Any contaminants including paints, curing compounds, oil, dirt and debris must be removed prior to application. Although TK-EPOXY CRACK AND JOINT FILLER is moisture tolerant, there cannot be standing water in or around the area to be filled at the time of application.

APPLICATION:

Air and substrate temperatures must be 50°F or above at the time of application.

Bulk Application - Components "A" and "B" must be stirred prior to use.

Cartridge Application - Shake the cartridge and remove the nut and cartridge plugs. Attach static mixer to cartridge and replace the nut. Install cartridge into mix gun and squeeze the trigger to begin flow of the material. Discard the first 1/2 to 1 ounce of material until the resulting mixture appears uniform. Place mixer tip into the area to be filled and squeeze the trigger to begin product flow. Maintain steady pressure to ensure proper mixing.

When used on industrial floors with heavy load transfers, it is recommended to fill to the full depth of the crack or joint.

NOTE: Silica sand may be used to discontinue flow into cracks and joints.

DRY TIME*:

At 77°F, this product gels in 9-11 minutes. It is mass tack free in 1 hour, and thin film tack free in less than 3 hours.

*Gel times, cure times and thin film tack free times will be extended with cooler temperatures.

TECHNICAL DATA

Color:	Gray
Composition:	Amine/Epoxy
Non-Volatile Content:	99.9%
Gel Time* (77°F):	9-11 minutes
Mass Tack Free* (77°F):	1 hour
VOC Content:	< 1 g/l
A.I.M. Category:	This product is not currently regulated by 1999 Federal EPA VOC regulations
Applicable Standards:	ASTM D2240 Hardness, Shore A: 80-85

* Cooler temperatures will extend gel and tack free times

COVERAGE:

The following table is an estimate of coverage rates and should be used as a guideline only. The rates are in linear feet per gallon - any overfill that will be shaved off is considered extra material and does not count toward coverage.

Joint Width	1.5 inches	2 inches
3/16"	68 feet	51 feet
1/4"	51 feet	38 feet

Additional Coverage Info:

As supplied, each 600-ml cartridge will fill 36 cubic inches of cracks (or a crack that is 12 linear feet long, by 1/8" wide, by 2" deep).

As supplied, each 2-gallon kit will fill 462 cubic inches of cracks.

*Coverage rate will vary depending on the size of the crack and any waste overfilled.

CLEAN UP:

Spills of uncured material may be cleaned with TK-00 XYLENE*. Cured material is extremely chemically inert and should be scraped off surfaces before it cures. Discard any used static mixers and do not attempt to reuse.

LIMITATIONS:

- Air and substrate temperatures must be 50°F or higher at the time of application.
- Shelf life is approximately 18 months from date of manufacture when stored at room temperature in an unopened container.

SAFETY PRECAUTIONS:

- This product contains chemicals that are corrosive and sensitizers. Care should be taken to minimize exposure and contact. Keep out of reach of children.
- Protective equipment such as safety glasses, gloves and respirators are recommended when handling this material in confined spaces.
- Avoid skin contact. If contact occurs, remove contaminated clothing immediately and wash skin with soap or a lanolized cleaner.
- Avoid eye contact. If contact occurs, flush eyes with large amounts of water and get medical attention immediately.

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

AVAILABILITY:

TK-EPOXY CRACK & JOINT FILLER is available through TK Distributors. Contact TK Products for the nearest distributor.

Packaged in 10-gallon kits, 2-gallon kits and 600-ml cartridges (approximately 20-fl. oz. each - boxed 12 cartridges per case).

FOR PROFESSIONAL USE ONLY

NOTES:

*TK-00 XYLENE must be purchased separately

01/16 Last Rev. 12/15

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.



TK Products Construction Coatings

11400 West 47th Street Minnetonka, MN 55343
800-441-2129 toll free | 952-938-8084 fax | www.tkproducts.com